



US009510713B2

(12) **United States Patent**
Farris, II

(10) **Patent No.:** **US 9,510,713 B2**
(45) **Date of Patent:** **Dec. 6, 2016**

(54) **METHODS FOR SEWING T-POCKET TOWELS**

(71) Applicant: **Joe Thomas Farris, II**, Lantana, TX (US)

(72) Inventor: **Joe Thomas Farris, II**, Lantana, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 96 days.

(21) Appl. No.: **14/467,337**

(22) Filed: **Aug. 25, 2014**

(65) **Prior Publication Data**

US 2016/0051097 A1 Feb. 25, 2016

(51) **Int. Cl.**
A47K 10/02 (2006.01)
A47C 31/11 (2006.01)

(52) **U.S. Cl.**
CPC **A47K 10/02** (2013.01); **A47C 31/11** (2013.01)

(58) **Field of Classification Search**
USPC 297/228.1, 228.11, 228.12, 228.13, 220,297/229
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D117,521 S * 11/1939 Freidman D2/719
2,441,745 A * 5/1948 Benamy A41B 13/06
15/227
3,111,677 A * 11/1963 Artzt A41B 13/00
2/69.5
3,559,874 A * 2/1971 Titchenal B65B 9/093
229/69

4,342,278 A * 8/1982 Horan B63B 7/08
114/345
4,477,930 A * 10/1984 Totten A61F 2/2409
623/2.15
4,826,011 A * 5/1989 Jud B65D 85/60
206/484
4,892,744 A * 1/1990 Ylvisaker B65D 81/3469
383/100
5,072,467 A 12/1991 Hunt
5,147,703 A * 9/1992 Provost A47K 10/02
15/209.1
5,316,337 A * 5/1994 Yamaji D05B 39/00
280/728.1
5,806,925 A * 9/1998 Hanley A47C 31/113
297/219.1
6,046,443 A * 4/2000 Ackerman 219/727
6,156,410 A * 12/2000 Bassler A41B 13/06
428/192
6,192,536 B1 2/2001 Connors
6,226,964 B1 * 5/2001 Vettorato B31B 29/00
383/94

(Continued)

Primary Examiner — David E Allred

(74) *Attorney, Agent, or Firm* — Elizabeth Philip Dahm; Kelly J. Kubasta; Ferguson Braswell & Fraser, PC

(57) **ABSTRACT**

The present invention includes a method to sew a “T” shaped pocket into a towel to orient, support and secure a towel draped over a seat back or frame structure which is an capable being accessibly and removably coupled to suitable objects, such as car seats and other seating having back rests or frames used to display advertising messages or items placed on display resting in the T-pocket. The T-pocket component may include a first end and a longer second end, the longer second end employed to provide a level of protection for the underlying seat and comfort to the seated person, but also allow the person to dry himself and maintain warmth.

17 Claims, 6 Drawing Sheets

